



BARRIER® M UV SYSTEMS

WALLACE & TIERNAN® UV DISINFECTION SYSTEMS

The Barrier® M range of UV systems is primarily designed for the treatment of water with flow rates ranging from 10 to 1150 m³/h (44 to 5000 US gpm). It is equipped with Wallace & Tiernan® medium-pressure lamps, type WTL and electrical ballasts. The wide emission spectrum of the lamps, ranging from 200 to 300 nm, attacks the nucleic acid (DNA), cell wall, proteins and enzymes of waterborne pathogens. Such attacks not only inactivate the microorganism by preventing the replication of its DNA, but also destroy its repair mechanisms. The Barrier® M system reaction chamber is characterized by optimal hydraulics and low pressure loss, ensuring a high efficiency of the UV system.

Applications

- Potable water
- Swimming pools, including chloramines reduction and disinfection
- Industrial process and wastewater, e.g. food & beverage, pharmaceutical, and fish hatcheries
- Small and medium size wastewater plants

Standard Features

- Optimized operation through stepless lamp power control
- Absolute calibrated UV sensor for optimal performance control
- Hydrodynamically optimized chamber design
- Simple, easy-to-use user interface
- Reaction chamber made of stainless steel AISI 316L, particular systems made of 318 LN for seawater available
- Automatic cleaning system (manual cleaning only available for Barrier M 35 systems)

Key Benefits

- Low operation costs and low head loss through low number of powerful medium-pressure lamps
- Extended lamp life and energy efficient operation through accurate lamp power control
- Low installation costs through space saving design and small footprint, easy installation and retrofit with in-line design
- Wide UV spectrum leads to effective treatment of photoreactivation
- Low life cycle costs with hydrodynamically optimized chamber design

Optional Feature

- Chemical cleaning system

TECHNICAL DATA

BARRIER® M SERIES OF UV SYSTEMS

Model	Disinfection capacity ¹		Chloramine reduction capacity ²	Connection flange acc. DIN EN 1092-1 ANSI	WTL Lamps	Weight dry	Dimensions UV chamber (A x H x L) ³	Electrical supply
		T _{10mm}						
M 35	33 m ³ /h 145 US gpm	98%	19 m ³ /h 84 US gpm	DN 80 3" 150-lb	1x1000/1001	14 kg 31 lbs	300 x 214 x 600 mm 11-13/16" x 8-7/16" x 23-10/16"	1/N/PE AC 208-277 V, 50-60 Hz (IEC) 2/PE AC 208-277 V, 50-60 Hz, 2-phase 2-wire (USA)
M 80	70 m ³ /h 308 US gpm	98%	39 m ³ /h 172 US gpm	DN 125 5" 150-lb	1x1000/1001	59 kg 130 lbs	350 x 306 x 1000 mm 11-13/16" x 8-7/16" x 39-3/8"	
M 135	112 m ³ /h 493 US gpm	98%	61 m ³ /h 269 US gpm	DN 125 5" 150-lb	1x2000/2001	59 kg 130 lbs	350 x 306 x 1000 mm 13-4/5" x 12" x 39-2/5"	
M 275	223 m ³ /h 982 US gpm	98%	119 m ³ /h 524 US gpm	DN 200 8" 150-lb	1x2000/2001	63 kg 139 lbs	400 x 406 x 900 mm 15-3/4" x 16" x 35-1/2"	3/N/PE AC 360/208-480/277 V, 50-60 Hz (IEC) 3/PE AC 208-277 V, 50-60 Hz, 3-phase 3-wire (USA)
M 210	116 m ³ /h 511 US gpm	90%	n.a.	DN 125 5" 150-lb	4x1000/1001	60 kg 132 lbs	350 x 306 x 1000 mm 13-4/5" x 12" x 39-2/5"	
M 290	106 m ³ /h 467 US gpm	85%	n.a.	DN 125 5" 150-lb	3x2000/2001	60 kg 132 lbs	350 x 306 x 1000 mm 13-4/5" x 12" x 39-2/5"	
M 350	130 m ³ /h 572 US gpm	85%	n.a.	DN 125 5" 150-lb	4x2000/2001	60 kg 132 lbs	350 x 306 x 1000 mm 13-4/5" x 12" x 39-2/5"	
M 525	337 m ³ /h 1484 US gpm	98%	176 m ³ /h 775 US gpm	DN 200 8" 150-lb	2x2000/2001	64 kg 141 lbs	400 x 406 x 900 mm 15-3/4" x 16" x 35-1/2"	
M 700	313 m ³ /h 1378 US gpm	90%	295 m ³ /h 1299 US gpm	DN 200 8" 150-lb	3x2000/2001	64 kg 141 lbs	400 x 406 x 900 mm 15-3/4" x 16" x 35-1/5"	
M 900	298 m ³ /h 1312 US gpm	85%	n.a.	DN 200 8" 150-lb	4x2000/2001	64 kg 141 lbs	400 x 406 x 900 mm 15-3/4" x 16" x 35-1/2"	
M 950	n.a.		402 m ³ /h 1770 US gpm	DN 250 10" 150-lb	3x2000/2001	72 kg 159 lbs	400 x 406 x 900 mm 15-3/4" x 16" x 35-1/5"	
M 1200	n.a.		528 m ³ /h 2325 US gpm	DN 250 10" 150-lb	4x2000/2001	72 kg 159 lbs	400 x 406 x 900 mm 15-3/4" x 16" x 35-1/2"	
M 1250	320 m ³ /h 1409 US gpm	80%	n.a.	DN 200 8" 150-lb	6x2000/2001	64 kg 141 lbs	400 x 406 x 900 mm 15-3/4" x 16" x 35-1/2"	
M 1400	493 m ³ /h 2171 US gpm	90%	n.a.	DN 350 14" 150-lb	2x3500/3501	160 kg 353 lbs	600 x 590 x 1000 mm 23-5/8" x 23-1/4" x 39-3/8"	
M 1700	n.a.		653 m ³ /h 2875 US gpm	DN 350 14" 150-lb	4x2000/2001	160 kg 353 lbs	600 x 590 x 1000 mm 23-5/8" x 23-1/4" x 39-3/8"	
M 2000	709 m ³ /h 3122 US gpm	90%	750 m ³ /h 3302 US gpm	DN 350 14" 150-lb	3x3500/3501	160 kg 353 lbs	600 x 590 x 1000 mm 39-2/5" x 23-1/4" x 39-2/5"	
M 2600	923 m ³ /h 4064 US gpm	90%	974 m ³ /h 4288 US gpm	DN 350 14" 150-lb	4x3500/3501	160 kg 353 lbs	600 x 590 x 1000 mm 39-2/5" x 23-1/4" x 39-2/5"	
M 3800	912 m ³ /h 4015 US gpm	85%	n.a.	DN 350 14" 150-lb	6x3500/3501	160 kg 353 lbs	600 x 590 x 1000 mm 23-5/8" x 23-1/4" x 39-3/8"	

1 Capacity at a Fluence (UV dose) of 400 J/m², end of lamp life, at the specified UV transmittance, and based on the multiple point source summation method

2 Capacity at a Fluence of 600 J/m², end of lamp life, and a UV transmittance (254 nm; 1 cm cell) of 95 %

3 A x H x L: Assembly dimension x height x length

FOR EACH MODEL A DETAILED DATA SHEET IS AVAILABLE.



Auf der Weide 10, 89312 Günzburg, Germany

+49 (8221) 904-0 www.evoqua.com

Barrier and Wallace & Tiernan are trademarks of Evoqua, its subsidiaries or affiliates, in some countries.

All information presented herein is believed reliable and in accordance with accepted engineering practices. Evoqua makes no warranties as to the completeness of this information. Users are responsible for evaluating individual product suitability for specific applications. Evoqua assumes no liability whatsoever for any special, indirect or consequential damages arising from the sale, resale or misuse of its products.

© 2020 Evoqua Water Technologies GmbH Subject to change without notice WT.090.370.000.DE.PS.1220

Wallace & Tiernan® Products worldwide

Australia
+61 3 8720 6597
info.au@evoqua.com

Canada
+1 905 944 2800
canadainfo@evoqua.com

China
+86 21 6057 7247
sales.cn@evoqua.com

France
+33 1 41 15 92 20
wtfra@evoqua.com

Germany
+49 8221 9040
wtger@evoqua.com

Singapore
+65 6830 7165
sales.sg@evoqua.com

UK
+44 300 124 0500
info.uk@evoqua.com

USA
+1 856 507 9000
wt.us@evoqua.com